

DESCRIPTION

- Outdoor clocks with high brightness LED.
- Height of digits 25 cm, optimal viewing distance: 120 metres.
- Angle of vision: 160°.
- LED colour available: red, white or yellow.
- Setting by control pad 2 keys inside the clock or by wireless remote control 868.3MHz (option).
- Optional synchronisation: Minute impulse, DCF or GPS antenna (absolute time accuracy)
- Optional time distribution: AFNOR, DHF, NTP or PC.
- Single or double-sided display.



STANDARDS

- EN60950, EN55022, EN55024, EN301-489-3 (V1.4.1), EN300-220-2 (V2.1.2)

GENERAL FEATURES

- **Setting of luminosity**..... Automatic (sun, cloud or night).
- **Setting of alternation duration**..... 2 to 6 seconds.
- **Display of time**..... date and temperature, counting / countdown, rate of chlorine, rate of humidity. Fix or alternate (manual input for the rate of chlorine and humidity).
- **Time display**..... 12 or 24 h mode.
- **Time changeover**..... Automatic summer/winter.
- **Temperature display**..... In Celsius (°C) or Fahrenheit (°F) from -99° to +99.9°.
- **Display**..... °C or °F in the menu. Display resolution: 0.1°C.
Accuracy: ±0.5°C from -10 to +85°C.
Offset adjustment, possible from - 9.9° to + 9.9°.
Display test menu.
- **869 MHZ HF temperature option**..... 50 meters communication distance (through a wall).
Transmission of the data to the clock every 15 seconds.

MECHANICAL FEATURES

- **Construction**..... Black aluminium casing. IP 54, IK 07.
- **Window**..... Antiglare protection glass.
- **Operating temperature**..... -20°C to +50°C.
- **Humidity**..... 93% at 40°C.
- **Electronic cards**..... Tropicalized.
- **Mounting**..... Wall mounted or optional bracket.
- **Weight**..... Single-sided: 11 kg. Double-sided: 30 kg.



Option: wireless remote control

ELECTRICAL FEATURES

- **Power supply**..... 100-240VAC 50/60HZ.
- **Rated current**..... 0.5A to 100VAC ; 0.25A to 240VAC single-sided.
0.6A to 100VAC ; 0.35A to 240VAC double-sided (with repeater).

SYNCHRONISATION OPTIONS


- **939 051**..... AFNOR/IMPULSE synchronisation card
- **939 052**..... DHF receiver (with antenna) for HF temperature and DHF time
- **939 053**..... PC / ASCII synchronisation card for data display
- **939 057**..... NTP synchronisation card
- **939 056**..... AFNOR synchronisation card

REFERENCES

- **939 343***..... HMT LED 25 cm
- **939 249***..... HMT LED 25 cm slave display
- **935 011**..... Temperature probe (with 5m cable)
- **939 032**..... Double-sided bracket HMT LED 25 cm
- **939 047**..... Wireless remote control
- **939 041**..... Wireless Temperature Probe
- **939 045**..... Wired Air Temperature / Humidity probe (5m cable)
- **915 296**..... Synchronisation cable kit (to synchronise 2 HMT that are not attached)



*Add the letter corresponding to the colour: R = red, J = yellow, W = white.

WALL MOUNTING



MOUNTING ON HANGING BRACKET

- The hanging bracket makes it possible to hang the clock from the ceiling or from the wall.



Dimensions in mm

Réf.: 643981T10/19