


DESCRIPTION

- Indoor or outdoor clocks available in various sizes and colours. High brightness LED.
- LED colour available : red (R).
- Display in hours (45 cm), minutes (45 cm) and seconds (45 cm).
- Setting by control pad 2 keys inside the clock or by wireless remote control 868.3MHz (option).
- Optional radio synchronisation: DCF or GPS antenna (absolute time accuracy), AFNOR, DHF, NTP or PC.
- Only single display.



STANDARDS

- EN60950, EN55022, EN55024, EN301-489-3 (V1.4.1), EN300-220-2 (V2.1.2)

GENERAL FEATURES

- **Optimal viewing distance**..... 200 metres with a viewing angle of 160°.
- **Setting of luminosity**..... Automatic (sun, cloud or night).
- **Setting of alternation duration**..... 2 to 6 seconds.
- **Display of time**..... date and temperature, counting / countdown, rate of chlorine, rate of humidity. Fix or alternate (manual input for the rate of chlorine and humidity).
- **Time display**..... 12 or 24 h mode.
- **Time changeover**..... Automatic summer/winter.
- **Temperature display**..... In Celsius (°C) or Fahrenheit (°F) from -99° to +99.9°.
- **Display**..... °C or °F in the menu. Display resolution: 0.1°C.
Accuracy: ±0.5°C from -10 to +85°C.
Offset adjustment, possible from - 9.9° to + 9.9°.
Display test menu.

MECHANICAL FEATURES

- **Construction**..... Black aluminium casing. IP 54, IK 07.
- **Window**..... Antiglare protection glass.
- **Operating temperature**..... -20°C to +50°C.
- **Humidity**..... 93% at 40°C.
- **Electronic cards**..... Tropicalized.
- **Mounting**..... Wall mounted or optional bracket.
- **Weight**..... 24 Kg.



Option: wireless remote control

ELECTRICAL FEATURES

- **Power supply**..... 100/240VAC 50/60HZ.
- **Rated current**..... 1A to 100VAC ; 0.55A to 240VAC.

REFERENCES

- 939 463R..... HMS LED 45 cm - red
- 939 463J..... HMS LED 45 cm - yellow
- 939 463W..... HMS LED 45 cm - white
- 939 047..... Wireless remote control
- 935 011..... Temperature probe (with 5m cable)

WALL MOUNTING

